

**Excavator Heavy Equipment  
Pre-use Inspection Form**

2012

PASS  FAIL (Submit failed equipment documentation to CO)

**Incident Name** \_\_\_\_\_

**Incident #** \_\_\_\_\_ **E #:** \_\_\_\_\_

**Vendor Name:** \_\_\_\_\_ **Agreement #** \_\_\_\_\_

**Equipment VIN/Unit ID#** \_\_\_\_\_

**Yes:**  **No:**  **Equipment VIN/Unit ID# matches RESOURCE ORDER**

**Inspector: (print)** \_\_\_\_\_ **Agency:** \_\_\_\_\_

**Signature:** \_\_\_\_\_ **Date:** \_\_\_\_\_

**Operator Name (print)** \_\_\_\_\_

**Operator Signature:** \_\_\_\_\_ **Date:** \_\_\_\_\_

**Yes:**  **No:**  **Vehicle Truck /Trailer Passes Safety Inspection: (OF-296)**

-----  
**Information to be provided by contractor at check-in. (D.8)**

Yes  No  The Contractor shall carry a minimum of two copies of the complete Agreement at all times.

**D.2 Equipment Requirements** (Mandatory)

Yes  No  Equipment shall meet all standards established by specification or incorporated by reference and shall be maintained in good repair by the Contractor.

Yes  No  An audible reverse warning device (backup alarm) of 87 decibel or greater at 5 feet behind and in the center of the equipment.

Yes  No  A fire extinguisher, multi-purpose 2A 10BC that is securely mounted to the vehicle and accessible by the operator. A current annual inspection tag.

Yes  No  Shovel

Yes  No  Forest Service qualified spark arrester on all naturally aspirated engines.

Yes \_\_\_ No \_\_\_ Radiator protection.

Yes \_\_\_ No \_\_\_ Seat belts.

Yes \_\_\_ No \_\_\_ Flashlight.

Yes \_\_\_ No \_\_\_ Water, 1 gal drinking.

Yes \_\_\_ No \_\_\_ 5 person first aid kit.

Yes \_\_\_ No \_\_\_ Personal Protective Equipment (Boots, Hard Hat, Gloves, Eye Protection, Hearing Protection, Head Lamp, New Generation Fire Shelter)

**D.2.1.2.2 Excavators shall have:** (Mandatory)

Yes \_\_\_ No \_\_\_ Operator Protection System. Shall have a factory enclosed canopy with deflectors installed in front of the operator area to deflect whipping saplings, branches and debris broken off by action of the bucket or hydraulic thumb. Deflectors shall be located so as not to impede visibility and access to the cab but still protect the operator from frontal damage.

Yes \_\_\_ No \_\_\_ Capability of operating at manufacturer’s limitations (i.e. slope).

Yes \_\_\_ No \_\_\_ Lighting (2 forward). Lights shall be mounted to the equipment in such a way to provide protection from damage and provide illumination beyond the bucket/thumb.

Yes \_\_\_ No \_\_\_ Hydraulic thumb or clamshell.

Yes \_\_\_ No \_\_\_ Steel Tracks.

**D.3.1 Training/Experience** (Mandatory)

Yes \_\_\_ No \_\_\_ Each person under this agreement shall meet the following minimum requirements:

1. RT-130 Annual Fireline Refresher including fire shelter.

**Comments:**

---



---



---



---



---



---



---