

#### Section 1 Identification

Trade Name:

Cut & Tap Fluid

**Product Identification:** 

4678

Synonyms:

Blend of Petroleum Distillates

**Product Use Description:** 

Lubricant

General Info Phone: (800) 795-9222 Emergency Phone: (800) 535-5053

Supplier:

ABC Compounding Co., Inc. 6970 JONESBORO RD Morrow, GA 30260

#### Section 2 Hazards Identification

#### Classifications

Aspiration Hazard - Category 1

Skin Irritation - Category 2

Eye Irritation - Category 2

Specific Target Organ Toxicity (single exposure) - Category 3

Flammable Aerosols - Category 1

Gasses under pressure - Liquefied gas







Flammable

Compressed Gas

Imitant

Heatth Hazard

Signal Word:

Danger

#### **Hazard Statements**

Keep out of reach of children.

Read label and SDS before use.

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

May be fatal if swallowed and enters airways.

May cause drowsiness or dizziness.

Causes skin irritation

Causes serious eye irritation.

#### **Precautionary Statements**

#### Prevention

Avoid breathing mist/spray.

Use only outdoors or in a well-ventilated area.

Keep away from heat, sparks, open flames and hot surfaces. □ -No smoking.

Do not spray on an open flame or other ignition source.

Pressurized container: Do not pierce or burn, even after use.

Wash hands thoroughly after handling.

Wear protective gloves.

Wear eye protection.



ir SWALLOWED: Immediately call a poison center or a doctor. Do NOT induce vomiting.

IF ON SKIN: Wash with plenty of soap and water.

If skin irritation occurs get medical attention.

Take off contaminated clothing and wash it before reuse.

Page 1 of 6 Trade Name: SDS #: 4678 Cut & Tap Fluid Revision Date 05/07/2015 SDS ID SDS00288



## **Safety Data Sheet**

### Cut & Tap Fluid

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

If eye irritation persists: Get medical attention.

IF INHALED: Remove person to fresh air and keep comfortable for breathing.

Call a poison center or a doctor if you feel unwell.

#### Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Store in a well-ventilated place.

Store locked up.

#### Disposal

Dispose of contents and container in accordance with all local, regional, and national regulations.

#### **Hazards Not Otherwise Specified**

Not applicable

#### Section 3 Composition

		Concentration
Chemical Name	CAS#	% by Weight
Hydrotreated Paraffinic Distillate	64742-54-7	>=50 <= 70
Light Hydrotreated Petroleum Distillate	68410-97-9	>=10 <= 20
Propane	74-98-6	>=10 <= 20
Kerosene	8008-20-6	>=1 <= 5
Butane	106-97-8	>=1 <= 5

#### Section 4 First Aid

#### **EMERGENCY OVERVIEW**

DANGER. Extremely flammable. Contents under pressure. Harmful or fatal if swallowed. Aspiration hazard if swallowed. Vapor harmful. Keep away from heat and flame. Can cause nervous system depression.

EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. If eye irritation persists: Get medical attention.

SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs get medical attention. Take off contaminated clothing and wash it before reuse.

INHALATION: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.

INGESTION: Harmful or fatal if swallowed. Seek medical attention immediately. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

### Section 5 Fire Fighting Measures





#### Suitable fire extinguishing media:

Use water spray, fog or foam.

#### Specific hazards arising from the chemical:

Flammable aerosol. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of subsequent explosion. Gas may accumulate in low or confined areas or travel a considerable distance to a source of ignition and flash back, causing fire or explosion. Bursting aerosol containers may be propelled from a fire at high speed. Runoff to sewer may create fire or explosion hazard.

#### Hazardous thermal decomposition products:

Carbon Dioxide, Carbon Monoxide

#### Specific fire-fighting methods:

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool.

#### Special protective equipment for fire fighters:

Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in a positive pressure mode.

### Section 6 Accidental Release Measures

#### Personal precautions:

Put on appropriate personal protective equipment (see section 8)

#### Environmental precautions and clean-up methods:

Stop all leaks. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Eliminate all ignition sources. Disperse vapors with water spray. Prevent runoff from entering drains, sewers, streams or other bodies of water. Absorb spill with inert material. Absorb unrecoverable product. Transfer contaminated absorbent, soil and other materials to containers for disposal.

#### Section 7 Handling and Storage

Do not use or store near heat, sparks or open flame. Exposure to temperatures above 120 F may cause bursting. Do not puncture or incinerate container. Store in a cool, dry place. Do not get in eyes, on skin or on clothing. Intentional misuse by deliberately concentrating and inhaling may be harmful or fatal. Keep out of reach of children.

#### Section 8 Exposure Controls/Personal Protection

 Trade Name:
 Cut & Tap Fluid
 SDS #:
 4678
 Page 3 of 6

 SDS ID:
 SDS00288
 Revision # 1
 Revision Date 05/07/2015



Butane

**ACGIH TLV** 1000 ppm

Hydrotreated Paraffinic Distillate

**ACGIH TLV** 5 mg/m3

**OSHA PEL** 5 mg/m3 (mist)

Kerosene

**ACGIH TLV** 200 mg/m3

**Propane** 

**ACGIH TLV** 1000 ppm

Eye Protection: Wear safety glasses or goggles.

Skin Protection: To prevent repeated or prolonged contact, wear impervious gloves (made from rubber, nitrile or neoprene).

Respiratory Protection: When respiratory protection is required use an organic vapor cartridge. A respiratory program that

meets OSHA's 29 CFR 1910.34 & ANSI Z88.2 requirements must be followed.

Engineering Controls: Good general ventilation required.

#### Section 9 Physical and Chemical Properties

**Property** Value

Appearance **CLEAR SPRAY/MIST Auto Ignition Temp NOT AVAILABLE Boiling Point NOT AVAILABLE** Color **COLORLESS Decomposition Temperature NOT AVAILABLE Evaporation Rate NOT AVAILABLE Explosive Limit Ranges** NOT AVAILABLE **Explosive Properties** NOT AVAILABLE Flash Point < 50 F (liquid portion) Melting/Freezing Point NOT AVAILABLE Odor SOLVENT

Odor Threshold **NOT AVAILABLE** Other Information VOC content (wt. %): 31 **Oxidizing Properties NOT AVAILABLE** 

**Partition Coeff** NOT AVAILABLE Physical State LIQUID Relative Density Solubility (Water) **INSOLUBLE** 

Vapor Density NOT AVAILABLE Vapor Pressure NOT AVAILABLE Viscosity NOT AVAILABLE pН NOT APPLICABLE

#### Section 10 Stability and Reactivity

Reactivity: Under normal conditions of storage and use, hazardous reactions will not occur.

**Chemical Stability:** Stable under normal conditions. Incompatible Materials: Acids and strong oxidizers

Conditions to Avoid: High temperatures, open flames, sparks, welding.

**Decomposition Products:** CO, CO2

Vapors may ignite at temperatures exceeding flash point.

#### Section 11 Toxicological Information


Primary Route of Entry: Skin contact, inhalation

SDS00288

Acute/Potential Health Effects:

EYES: May cause serious eye irritation. Symptoms include stinging, tearing and redness.

SKIN: May cause skin irritation. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, drying of skin and skin burns.







INHALATION: High vapor/aerosol concentrations (>1000 ppm) are irritating to the eyes and respiratory tract. May cause headaches, dizziness, anesthesia, drowsiness, unconsciousness, and other central nervous system effects, including death. May cause peripheral nervous system disorder and/or damage.

**INGESTION:** Harmful or fatal if swallowed. Aspiration hazard - this material can enter lungs during swallowing or vomiting and cause lung inflammation and damage.

Chronic / Long Term Effects: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Signs and Symptoms of Overexposure: Signs and symptoms of overexposure to this material through breathing, swallowing, and/or passage of material through the skin may include: stomach or intestinal upset (nausea vomiting, diarrhea) irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness).

Target Organ Effects: Central nervous system.

Reproductive/Developmental Information: None known

Carcinogenic Information: This material is not listed as a carcinogen by IARC, NTP or OSHA.

**Acute Toxicity Values:** 

Not available.

## Section 12 Ecological Information

Not available.

### Section 13 Disposal Considerations

Waste must be disposed of in accordance with federal, state and local environmental control regulations. See label for further instructions.

#### Section 14 Transport Information

Certain shipping modes or package sizes may have exceptions from the transport regulations. The classification provided may not reflect those exceptions and may not apply to all shipping modes or package sizes.

UN number 1950

Proper shipping name Aerosols, flammable

Class 2.1

Packing group

## Section 15 Regulatory Information

S

#### on 16 Other Information

**HMIS Ratings:** 

 Trade Name
 Cut & Tap Fluid
 SDS #:
 4678
 Page 5 of 6

 SDS ID
 SDS00288
 Revision # 1
 Revision Date 05/07/2015





Disclaimer: This Manufacturer believes that the information contained in the Safety Data Sheet is accurate. The suggested procedures are based on experience as of the date of the publication. They are not necessarily all inclusive nor fully adequate in every circumstance. Also, the suggestions should not be confused with, nor followed in violation of applicable laws, regulations, rules or insurance requirements.

Preparation/Revision Date: 5/7/15

