DATE:

TIME:

CONTRACT FIRE EQUIPMENT - INCIDENT INSPECTION CHECKLIST

FIRE NAME:	INCIDENT NUMBER:	RESOURCE #:		
COMPANY/CONTRACTOR:				
CONTRACT/AGREEMENT #:	Equipme	ent/Company I.D. #		
VIN#:	LICENCE PLATE, State and #:	<i>Exp</i>		
OPERATOR NAME:	DRIVERS LICENCE, State and #:	Exp: lass: Endorsements:		

EQUIPMENT and OPERATOR REQUIREMENTS – SUPPORT WATER TENDER

#	Minimum Requirements	Pass	Fail
	(Not all inclusive, for additional items and clarification refer to contract – Section D)		
1	Two copies of <u>complete</u> Agreement/Contract: One for finance, one in truck (D.8)		
2	Completed Check-In Process: Which also includes, Finance, and Plans (D.6.5.3) (D.8)		
3	VIN/Equipment# on Contract/Agreement and Resource Order matchesVIN/Equipment# on this Water Tender(D.6.2)(D.6.3.1)		
4	Vehicle successfully completed Mechanical, OF-296 Inspection (Vehicle/Heavy Equipment Safety Inspection) at this incident, completed OF-296 form in vehicle (D.17) (D.17.1)		
5	Vehicle meets licensing requirements (D.2.1.2) (D.2.2) (D.4)		
6	Current DOT vehicle inspection or CVSA inspection: Date: (D.2.2)		
7	Operator of Vehicle Properly licensed (D.2.2) (D.6.6)		
8	RT-130 Fire Line Refresher including Fire Shelter (current) (D.3.1_1) DATE: AGENCY/LOCATION:		
9	Company Name: Permanently affixed to both sides of truck, (at least 2 inches lettering). (D.2.2.3)		
10	Equipment/Company I.D. #: Permanently affixed to both sides of truck, (at least 2 inches lettering). (D.2.2.3)		
11	Seat Belt(s): For all passengers (D.2.1.2) (Exhibit M)		
12	Programmable Radio: If handheld, also needs two battery clamshells (D.2.3) (Exhibit M)		
13	Reflective Triangles: Directional set of 3 (Exhibit M)		
14	Fire Extinguisher: Multi-purpose, 2A 10BC, with current inspection tag. Securely mounted to vehicle and accessible by the operator (D.2.1.2) (Exhibit M)		
15	First aid kit: 5 person minimum (D.2.1.2) (Exhibit M)		
16	Flashlight/Portable Hand Light (working) (D.2.1.2) (Exhibit M)		
17	PPE: Boots, Hard Hat, Gloves, Eye Protection, Hearing Protection, Headlamp with batteries (D.2.1.2)		
18	Fire Shelter: New generation(D.2.1.2)		
19	Flame Resistant Clothing (Nomex): Two Full Sets (D.2.1.2)		

#	Minimum Requirements - continued	Pass	Fail			
20						
21	Reducer , 1 ¹ / ₂ inch NH female to 1 inch NPSH male: 1 each (Exhibit M)					
22	Adapters 1 ¹ / ₂ inch NPSH female to 1 ¹ / ₂ inch NH male: 2 each (Exhibit M)					
23	Adapters 1 ¹ / ₂ inch NH female to 1 ¹ / ₂ inch NPSH male: 2 each (Exhibit M)					
24	Reducers 2 ¹ / ₂ inch NH female to 1 ¹ / ₂ inch NH male: 2 each (Exhibit M)					
25	Double male 1 ½ inch NH: 1 each(Exhibit M)					
26	Double Female 1 ½ inch NH: 1 each(Exhibit M)					
27	Gated "Y" 1 ½ NH: 1 each (Exhibit M)					
28	Fire Hose Clamp 2 ½ inch: 1 each(Exhibit M)					
29	Spanner Wrench, Combination 1 ¹ / ₂ inch to 2 ¹ / ₂ inch: 1 each (Exhibit M)					
30	Adjustable Hydrant Wrench: 1 each(Exhibit M)					
31	Shovel – Size 0 or 1: 1 each (Exhibit M)					
32	Pulaski: 1 each(Exhibit M)					
33	100 foot – 1 ¹ / ₂ inch Cotton/Synthetic Hose NH Thread (D.7.1.3) (Exhibit M)					
34	50 Foot – 2 ¹ / ₂ inch Cotton/Synthetic Hose NH Thread (D.7.1.3) (Exhibit M)					
35	Suction hose with strainer or screened foot valve: 20 foot minimum (D.7.1.3) (Exhibit M)					
36	Wheel Chocks: At least one pair, meeting specifications (Exhibit M)					
37	Tank Baffling: Meets specifications. Measured Partitions Free Floating Baffle					
20	System (baffle balls), Note: If Baffle Balls, Does operator have manufactures compliance certificate or invoice (D.2.1.2)					
38	Dump Valve: Minimum 4 inch. Extends past rear of vehicle. (D.2.1.2.2)					
39	Pump: Discharge Pressure Gauge: (D.2.1.2)					
40	Auxiliary pump (if equipped): Fuel to operate for at least 12 Hours. (Exhibit M)					
41	2 ¹ / ₂ inch Discharge Outlet, national hose thread: 1 each (Exhibit M)					
42	1 ¹ / ₂ inch Discharge Outlet, national hose thread: 2 each (Exhibit M)					
43	Spray Bar head(s) operational: (D.2.1.2.2.1) (D.4) (Exhibit J) (Exhibit M) Spray Bar Configuration: Front Rear Both Gravity or Pressure					
44	Back-Up Alarm: Audible reverse warning device. (D.2.1.2)					
	YesContract Deficiencies FoundNoContract Deficiencies Found					
	Contractor is given the opportunity (<i>Optional</i>), to correct noted deficiencies. May be given the opportunity (<i>Optional</i>), the correct noted deficiencies.	up to 24	Hours			
	as of:	1				
	Date:Time:See Remarks (D.7.1.	.1) (D.17)			
	Contactor successfully corrected deficiencies: Date: <u>Time:</u>					
	Contactor successfully corrected deficiencies Date: Inspector:					
REMARKS:						
COP						
	TRACTOR REPRESENTATIVE: Title: (Print and Sign) (Print and Sign)		-			
GOVERNMENT INSPECTOR: Title:						